

NEBULA SERIES

MONO PERC 108-cell MODULE

EG-300M54-HL-WB.A

300W

ADVANTAGE DESCRIPTION

Free color

multiple colors are available, stable without color difference

Extraordinary adaptability

Flexible configuration, suitable for various roof scenarios

KEY FEATURES



SMBB cell design

Super multi Busbar cells brings lower resisitance and increased Busbar reflectance ensures higher power output



PID Resistant

Excellent PID resistance performance optimized by unique structural design



High Reliability Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified



Excellent Low-light Performance

Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments



Highly Mechanical Load Design

Certified to withstand:5400Pa snow load and 2400Pa wind load





Low degradation Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-effeciency, greatly increased on generation performance




EG-300M54-HL-WB.A

Engineering Drawings





I-V Curves



Electrical Characteristics	
Power level	300
Pmax (W)	300
Vmp (V)	30.83
Imp (A)	9.75
Voc (V)	37.00
Isc (A)	10.39
FF (%)	78.20
Maximum system voltage (V)	1500
Fuse Rating (A)	25
Temperature coefficient Pmax (%/°C)	-0.29
Temperature coefficient Isc (%/°C)	0.046
Temperature coefficient Voc (%/°C)	-0.24

Mechanical Characteristics	
Number of cells	108pcs
Size of cell (mm)	182*91
Type of cell	Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	1722*1134*30
Weight (kg)	20.2



Tel:86-519-82585880 Zip:213213 Add:No.18, Jinwu Road, Jintan Dist, Changzhou City, Jiangsu Province. Email:marketing@egingpv.com Web:www.egingpv.com

Revised in May 2025 1st Edition

CAUTION:All rights and explain reserved by EGING PV.

Specifications included in this datasheet are subject to change without notice.

The specific content of the product warranty refers to EGing's latest warranty.