

CERTIFICATE


TÜV NORD CERT GmbH
herewith declares that

Changzhou EGing Photovoltaic Technology Co., Ltd.
No.18, Jinwu Road, Yaotang Town, Jintan District
Changzhou City, Jiangsu Province 213213, P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:

Description of product (details see Annex 2):

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules



Valid from: 2025-02-21

Valid until: 2030-02-20

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC 61701:2020 / EN IEC 61701:2020
Remark:	Test Method 8
	Test duration: 1440 hours
Registered No.:	44 780 25 406749 - 051
Manufacturer and factory(-ies):	See Annex 1
Test Report No.:	492013657.001
File No.:	PVP08175/24P-08



TÜV NORD CERT GmbH
Certification Body
Consumer Products



Essen, 2025-02-21

Please also pay attention to the information stated overleaf.

Manufacturer and factory(-ies):

Manufacturer: **Changzhou EGing Photovoltaic Technology Co., Ltd.**
No.18, Jinwu Road, Yaotang Town, Jintan District
Changzhou City, Jiangsu Province 213213, P.R. China

Factory : **Changzhou EGing Photovoltaic Technology Co., Ltd.**
No.18, Jinwu Road, Yaotang Town, Jintan District
Changzhou City, Jiangsu Province 213213, P.R. China

Factory inspection report no.: 862010123.012

Remark:

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Description of product(s):

Module types: **Double-glass PV Modules with 210mm Bifacial Mono-crystalline Silicon half-cut Solar Cells:**
132 cells: EG-XXXNT66-HU/BF-DG (XXX=660-715, in increment of 5)
120 cells: EG-XXXNT60-HU/BF-DG (XXX=600-650, in increment of 5)

Maximum system voltage: 1500V

Maximum overcurrent protection rating: 35A

Electrical protection class: Class II

Module types: **Double-glass PV Modules with 182mm Rectangle Bifacial half-cut Mono-crystalline Silicon Solar Cells:**
144 cells: EG-XXXNT72-HRa/BF-DG (XXX=580-620, in increment of 5)
120 cells: EG-XXXNT60-HRa/BF-DG (XXX=480-510, in increment of 5)
108 cells: EG-XXXNT54-HRa/BF-DG (XXX=430-460, in increment of 5)
144 cells: EG-XXXNT72-HRb/BF-DG (XXX=575-610, in increment of 5)
120 cells: EG-XXXNT60-HRb/BF-DG (XXX=475-510, in increment of 5)
108 cells: EG-XXXNT54-HRb/BF-DG (XXX=425-460, in increment of 5)
132 cells: EG-XXXNT66-HRc/BF-DG (XXX=585-615, in increment of 5)

Maximum system voltage: 1500V

Maximum overcurrent protection rating: 30A or 35A

Electrical protection class: Class II

Remark:

For detailed product information, please refer to CDF (Constructional Data Form).



TÜV NORD CERT GmbH
Certification Body
Consumer Products